

2020 m. kovo mėn.	Viršutinis šilumingumas kWh/m ³		Perskaičiavimo koeficientas
	0 C° matavimo	20 C° matavimo	
1	11,8021	10,9910	1,0738
2	11,7824	10,9726	1,0738
3	11,7807	10,9710	1,0738
4	11,7904	10,9801	1,0738
5	11,4130	10,6286	1,0738
6	11,7758	10,9665	1,0738
7	11,7558	10,9478	1,0738
8	11,7534	10,9456	1,0738
9	11,7566	10,9486	1,0738
10	11,4022	10,6186	1,0738
11	11,7836	10,9737	1,0738
12	11,5852	10,7890	1,0738
13	11,3950	10,6118	1,0738
14	11,8034	10,9922	1,0738
15	11,8159	11,0038	1,0738
16	11,8233	11,0107	1,0738
17	11,7836	10,9737	1,0738
18	11,4209	10,6360	1,0738
19	11,7109	10,9060	1,0738
20	11,8154	11,0034	1,0738
21	11,8261	11,0133	1,0738
22	11,5052	10,7145	1,0738
23	11,6990	10,8950	1,0738
24	11,8130	11,0011	1,0738
25	11,8237	11,0111	1,0738
26	11,7682	10,9594	1,0738
27	11,7644	10,9559	1,0738
28	11,7687	10,9599	1,0738
29	11,7782	10,9687	1,0738
30	11,7785	10,9690	1,0738
31	11,7688	10,9600	1,0738
Vidurkis	11,7175	10,9122	-

* Skirstymo sistemos operatoriaus viršutinio dujų šilumingumo vertės nurodytos esant norminėms sąlygoms: +25 °C degimo temperatūrai, +20°C matavimo temperatūrai ir 101,325 kPa absoliutiniam slėgiui bei esant sausoms dujoms.