

2024-04-03  
 Mažeikiai

2024 m. kovo mėn.	Viršutinis šilumingumas kWh/m <sup>3</sup>		Perskaičiavimo koeficientas
	0 C° matavimo	20 C° matavimo	
1	11.3491	10.5691	1.0738
2	11.3514	10.5712	1.0738
3	11.3576	10.5770	1.0738
4	11.3591	10.5784	1.0738
5	11.3618	10.5809	1.0738
6	11.3521	10.5719	1.0738
7	11.3546	10.5742	1.0738
8	11.3565	10.5760	1.0738
9	11.3612	10.5804	1.0738
10	11.3679	10.5866	1.0738
11	11.3497	10.5697	1.0738
12	11.3486	10.5686	1.0738
13	11.3495	10.5695	1.0738
14	11.3517	10.5715	1.0738
15	11.3540	10.5737	1.0738
16	11.3534	10.5731	1.0738
17	11.3548	10.5744	1.0738
18	11.3588	10.5781	1.0738
19	11.3595	10.5788	1.0738
20	11.3599	10.5792	1.0738
21	11.3641	10.5831	1.0738
22	11.3728	10.5912	1.0738
23	11.3626	10.5817	1.0738
24	11.7258	10.9199	1.0738
25	11.7764	10.9670	1.0738
26	11.7678	10.9590	1.0738
27	11.7721	10.9630	1.0738
28	11.7811	10.9714	1.0738
29	11.7893	10.9790	1.0738
30	11.7891	10.9789	1.0738
31	11.7906	10.9803	1.0738
<b>Vidurkis</b>	<b>11.4646</b>	<b>10.6767</b>	-

\* Skirstymo sistemos operatoriaus viršutinio dujų šilumingumo vertės nurodytos esant norminėms sąlygoms: +25 °C degimo temperatūrai, +20°C matavimo temperatūrai ir 101,325 kPa absoliutiniam slėgiui bei esant sausoms dujoms.