

2024 m. liepos mėn.	Viršutinis šilumingumas kWh/m ³		Perskaičiavimo koeficientas
	0 C° matavimo	20 C° matavimo	
1	11.5409	10.7477	1.0738
2	11.5448	10.7514	1.0738
3	11.5460	10.7525	1.0738
4	11.5485	10.7548	1.0738
5	11.5511	10.7572	1.0738
6	11.5521	10.7581	1.0738
7	11.5534	10.7594	1.0738
8	11.5554	10.7612	1.0738
9	11.5636	10.7689	1.0738
10	11.6594	10.8581	1.0738
11	11.8117	10.9999	1.0738
12	11.8006	10.9896	1.0738
13	11.8023	10.9912	1.0738
14	11.8095	10.9979	1.0738
15	11.8209	11.0085	1.0738
16	11.8075	10.9960	1.0738
17	11.8188	11.0065	1.0738
18	11.7540	10.9462	1.0738
19	11.4552	10.6679	1.0738
20	11.4620	10.6742	1.0738
21	11.4631	10.6753	1.0738
22	11.4664	10.6783	1.0738
23	11.4506	10.6636	1.0738
24	11.4486	10.6618	1.0738
25	11.4520	10.6649	1.0738
26	11.4563	10.6689	1.0738
27	11.4484	10.6616	1.0738
28	11.4185	10.6337	1.0738
29	11.4207	10.6358	1.0738
30	11.4217	10.6367	1.0738
31	11.4238	10.6387	1.0738
Vidurkis	11.5751	10.7796	-

* Skirstymo sistemos operatoriaus viršutinio dujų šilumingumo vertės nurodytos esant norminėms sąlygoms: +25 °C degimo temperatūrai, +20°C matavimo temperatūrai ir 101,325 kPa absoliutiniam slėgiui bei esant sausoms dujoms.